



Greenville Fire Department

March

RUSSELL L. THOMPSON, FIRE CHIEF

Public Safety Announcement

Change Your Clock - Change Your Batteries

With daylight savings time approaching (March 10), the Greenville Fire Department urges you to install new batteries in each smoke and CO alarm (detector) in your home when you “spring forward” the time on your clocks. It has been proven that a working smoke alarm is the single most effective tool in surviving a house fire.



Types of Smoke Alarms

Ionization and Photoelectric smoke alarms detect different types of fires:

- Ionization smoke alarms are generally more responsive to flaming fires. The ionization unit uses “ions” or electrically charged particles, to detect smoke in the air. The greater amount of the smoke, the higher the electrical imbalance. The alarm will sound when the electrical imbalance reaches a preset level.
- Photoelectric smoke alarms are generally more responsive to fires that begin with a long period of smoldering. This type of alarm uses a beam of light and a light sensor in the sensing chamber. The sensing chamber is designed so that the light beam does not strike the sensor, but smoke particles entering the chamber deflect the light onto the sensor. The greater amount of smoke entering the chamber; the more light will be deflected onto the sensor. The alarm sounds when the amount of light hitting the sensor reaches a preset level.

- There are also smoke alarms for people with hearing loss. These alarms have strobe lights and/or vibrate to alert those who are unable to hear a standard smoke alarm.

Smoke Alarm Installation

Follow manufacturer's instructions for the best placement of your alarms. Smoke alarms should be installed:

- On each level within the home (including basement and habitable attics), utilizing photoelectric and ionization technologies or dual sensing smoke alarm.
- In each sleeping room.
- Outside each separate sleeping area in the immediate vicinity of the sleeping rooms, utilizing photoelectric technology.

Smoke Alarm Inspection

- Test smoke alarms monthly by pushing the test button on the detector.
- Clean your alarm at least once a year. Vacuum out the dust and cob-webs that have accumulated.
- Smoke alarms are powered by battery or by your home's electrical system. If the smoke alarm is powered by battery, it runs on either a disposable none-volt battery or a non-replaceable 10-year lithium ("long-life") battery. Even alarms that get power from your home's electrical system, or "hardwired alarms," usually have a back-up battery. All smoke alarm batteries (excluding the 10-year lithium batteries) need to be replaced twice a year. **Change Your Clock - Change Your Batteries.**

Smoke Alarm Protection

- Do not disable the smoke alarm or remove the batteries.
- Replace any smoke alarm that is past its 10 year service life.
- Have a family fire escape plan with a designated meeting place and practice your plan.
- Consider purchasing a long-life (lithium) battery-powered smoke alarm, which may last up to ten years with no battery change.
- Interconnected smoke alarms are best because if one sounds, they all sound.

Don't Have Working Smoke Alarms?

If you are a resident within the city limits of Greenville, we will install a working smoke alarm (photoelectric) in your residence. The program is free to those who qualify. For more information, please contact the Greenville Fire Department.

City of Greenville
Greenville Fire Department
100 Public Square | Greenville, Ohio 45331
(937) 548-3040
www.cityofgreenville.org